



PCB LAYOUT

Table (1)

Code	Definition	Code	Definition
1	Gold/Flash	A	Gold 1u"/Light Tin
2	Gold 3u"	B	Gold 3u"/Light Tin
3	Gold 5u"	C	Gold 5u"/Light Tin
4	Gold 10u"	D	Gold 10u"/Light Tin
5	Gold 15u"	E	Gold 15u"/Light Tin
6	Gold 30u"	F	Gold 30u"/Light Tin

NOTES:

- MATERIALS:
 - INSULATOR: Polyester UL94V-0.
 - CONTACT : BRASS.
 - PLATED: CONTACT GOLD PLATED OVER NI.
- ELECTRICAL CHARACTERISTICS:
 - CURRENT RATING: 3 Amp.
 - VOLTAGE RATING: 250V AC/DC.
 - CONTACT RESISTANCE: 20 mOhms MAX.
 - INSULATION RESISTANCE: 1000 MOhms MIN.
 - WITHSTANDING VOLTAGE: 500V AC/MINUTE.
 - Operation Temperature: -25° C~+105° C.

Part NO.

213-**-1*-002* -***

- Pin 数 04-80
- 端子脚长 Dim"A"x"B"
- 1:3.0x6.0
- 2:2.4x6.0
- 3:4.5x6.0
- 5:3.0x4.5
- 7:3.2x5.84
- 8:3.0x10.0
- 唛头 0:无 1:nextron 2:tyco
- 塑胶颜色 0:黑色 2:红色 4:黄色 6:蓝色
- 塑胶材质 0:PBT 1:LCP 4:PA 6T 5:PA 9T
- Plated See Table (1)

UNITS	NAME:
X ±0.5	2.54mm Pin Header Double Row
X ±0.38	
.XX±0.25	PART NO.: 213-**-1*-002* -***
.XXX±0.08	
X' ±2'	FINISH
	CHKD:
	DR: niezhengqi
	DATE: 09/07/13
	TITLE: 2.54mm Pin Header Double Row Straight Pin
	DWG NO.: EP-C-213-0010-0000
	SCALE: 1:1
	SHEET: 1/1
	REV: A1

REV.	EQN. NO.	APPD.	DATE
A0	RELEASE	Chang	09/07/13
A1	RELEASE	niezhengqi	09/07/13