


## Automotive Transil™, transient voltage suppressor (TVS) for LIN bus


Datasheet - production data



### Description

The device is an asymmetrical Transil diode designed specifically for one automotive LIN bus line against electrostatic discharge (ESD) protection. The SOD323 is a very small package that saves space on high density printed circuit board.

Transil diodes provide high overvoltage protection by clamping action and have instantaneous response to transient overvoltages.

 TM: Transil is a trademark of STMicroelectronics.

### Features


- AEC-Q101 qualified
- Asymmetrical bidirectional device
- Stand-off voltage:
  - - 15 V (to comply with reverse battery)
  - + 24 V (to comply with jump start)
- Low leakage current



### Complies with the following standards

- ISO 10605 (C = 150 pF, R = 330 Ω)
  - 30 kV (air discharge)
  - 30 kV (contact discharge)
- ISO 10605 (C = 330 pF, R = 330 Ω)
  - 30 kV (air discharge)
  - 30 kV (contact discharge)
- ISO 7637-3
  - Pulse 3a:  $V_s = -150$  V
  - Pulse 3b:  $V_s = 100$  V
- HBM MIL STD 833, class 3 (> 4 kV)
- ISO 17987-7 (LIN bus)
- SAE J3076 (CXPI bus)

Figure 1: Pin configuration



# 1 Characteristics

**Table 1: Absolute maximum ratings (limiting values)  $T_{amb} = 25^{\circ}C$**

Symbol	Parameter		Value	Unit
$P_{PP}$	Peak pulse power dissipation 8/20 $\mu s$	$T_j \text{ initial} = T_{amb}$	160	W
$T_{stg}$	Storage junction temperature range		-65 to +175	$^{\circ}C$
$T_j$	Maximum operating junction temperature		-40 to +150	
$T_L$	Maximum temperature for soldering during 10 s		260	$^{\circ}C$

**Table 2: ESD maximum ratings**

Symbol	Parameter	Conditions	Value	Unit
ESD	Electrostatic discharge capability	ISO 10605 (C = 150 pF, R = 330 $\Omega$ ) air discharge	30	kV
		contact discharge	30	
		ISO 10605 (C = 330 pF, R = 330 $\Omega$ ) air discharge	30	
		contact discharge	30	
		HBM MIL STD 833	10	

**Figure 2: Electrical characteristics (definitions)**









Table 3: Electrical characteristics ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ )





Symbol	Test conditions		Min.	Typ.	Max.	Unit
$V_{BR}$	From pin 2 to pin 1	$I_R = 5\text{ mA}$ , $t_p < 50\text{ ms}$	25.4	27.8	30.3	V
	From pin 1 to pin 2		17.1	18.9	20.3	
$I_{RM}$	From pin 2 to pin 1	$V_{RM} = 24\text{ V}$		1	50	nA
	From pin 1 to pin 2	$V_{RM} = 15\text{ V}$				
$V_{CL}$	From pin 2 to pin 1	$I_{PP} = 1\text{ A}$	8/20 $\mu\text{s}$		40	V
	From pin 2 to pin 1	$I_{PP} = 3\text{ A}$			50	
	From pin 1 to pin 2	$I_{PP} = 1\text{ A}$			25	
	From pin 1 to pin 2	$I_{PP} = 5\text{ A}$			35	
C	$V_R = 0\text{ V}$ , $f = 1\text{ MHz}$			16	20	pF
$\alpha T^{(1)}$	From pin 2 to pin 1				9.6	$10^{-4}/^{\circ}\text{C}$
	From pin 1 to pin 2				8.8	

**Notes:**

$$^{(1)}\Delta V_{BR} = \alpha T \times (T_{amb} - 25) \times V_{BR}(25^{\circ}\text{C})$$

### 1.1 Characteristics (curves)





## 2 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: [www.st.com](http://www.st.com). ECOPACK® is an ST trademark.

- Epoxy meets UL94, V0
- Lead-free package

### 2.1 SOD323 package information

Figure 12: SOD323 package outline







Table 4: SOD323 package mechanical data

Ref.	Dimensions			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A		1.17		0.046
A1		0.10		0.004
A2	0.93	1.01	0.037	0.040
b	0.25	0.44	0.01	0.017
c	0.10	0.25	0.004	0.01
D	1.52	1.80	0.06	0.071
E	1.11	1.45	0.044	0.057
HD	2.30	2.70	0.09	0.106
L	0.10	0.46	0.004	0.02
Q1	0.10	0.41	0.004	0.016

Figure 13: Footprint recommendations, dimensions in mm




## 2.2 SOD323 packing information





### 3 Placement and PCB layout recommendations

Below figure illustrates the PCB placement and layout recommendations for optimal benefits of the ESDLIN1524BJ.



## 4 Ordering information




Table 5: Ordering information

Order code	Marking	Package	Weight	Base qty.	Delivery mode
ESDLIN1524BJ	24	SOD323	5 mg	3000	Tape and reel
ESDLIN1524BJ-HQ				10000	

## 5 Revision history

**Table 6: Document revision history**

Date	Revision	Changes
28-Aug-2006	1	Initial release.
22-Sep-2006	2	Added Figure 6 Placement and layout recommendations
18-Jan-2013	3	Updated Table 6. Added Figure 10 and Figure 11.
17-Oct-2017	4	<p>Updated title and cover page.</p> <p>Updated <i>Table 1: "Absolute maximum ratings (limiting values) Tamb = 25° C"</i> and <i>Table 3: "Electrical characteristics (Tamb = 25 °C)"</i>.</p> <p>Added <i>Figure 8: "Response to ISO 7637-3 pulse 3a (Us = -150 V)"</i>, <i>Figure 9: "Response to ISO 7637-3 pulse 3b (Us = 100 V)"</i>, <i>Figure 10: "ESD response to ISO 16605 ( C = 150 pF, R = 330 Ω, 8 kV contact)"</i> and <i>Figure 11: "ESD response to ISO 16605 ( C = 150 pF, R = 330 Ω, 8 kV contact)"</i>.</p> <p>Minor text changes to improve readability.</p>

**IMPORTANT NOTICE – PLEASE READ CAREFULLY**

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2017 STMicroelectronics – All rights reserved

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[STMicroelectronics:](#)

[ESDLIN1524BJ](#) [ESDLIN1524BJ-HQ](#)